

Technical Data Sheet (TDS)

70020A

FLEET 15W/40 SL/CH4

V3 08/2015

Product Description:

Fleet 15W/40 SL/CH4 is a multigrade engine oil manufactured from carefully selected base oils and the latest additive technology. It meets the majority of the latest engine manufacturer's requirements and specifications. It can be supplied for most mixed fleet applications. Dispersant additives help maintain engine cleanliness in petrol engines and the detergent additives help reduce unwanted deposits in turbo charges and on pistons.

Benefits:

- High shear stability for stay in grade performance
- High thermal stability provides protection against piston deposits
- Improved bore polishing protection
- Anti-wear performance for reduced engine wear
- Ideal mixed fleet lubricant
- Sludge control for stop-go city motoring

Applications:

Fleet 15W/40 SL/CH4 is suitable for normally aspirated and turbo charged highly stressed petrol engines and diesel engines in the passenger cars and heavy commercials, vans, plant, buses and industrial equipment. It is miscible with all synthetic and mineral based engine oils.

Product Profile:

- ACEA: A3,B3,B4,E2,E3
- API: SL/CH-4
- MB: 228.1, 229.1
- Mack: EO-L
- MAN: 271
- MTU: Type 1
- Volvo: VDS-3
- VW: 505

Typical Test Data:

| | | |
|----------------------|---|-------|
| SG @ 15.6°C | - | 0.886 |
| KV @ 100°C (cSt) | - | 14.25 |
| KV @ 40°C (cSt) | - | 104.9 |
| VI | - | 146 |
| Flash Point COC (°C) | - | 215 |
| Pour Point (°C) | - | -30 |
| TBN (mgKOH/g) | - | 10.2 |

Contact for more information.

Unit 10, Greenhills Business Centre, Greenhills Road, Tallaght, Dublin 24
Office contact
Email: info@bardahl.ie
Tel: 01 - 404 9490



A product of **Bardahl** Distributors.