

Technical Data Sheet (TDS)

75220A

HIGH PERFORMANCE TRACTOR UNIVERSAL 10w/30

Product Description:

A premium quality multigrade super universal tractor oil manufactured from solvent refined paraffinic base oils blended with additives which are specially selected to give high performance in various applications on the modern tractor.

Benefits:

Universal application reduces lubricant stock levels and prevents misapplication
Reduced engine deposits and oil thickening. Improved wear protection
Excellent anti-corrosion properties which protects all working components

Applications:

Engine, transmission (including wet brakes) and hydraulic systems of agricultural tractors. Suitable for turbocharged and naturally aspirated diesel engines, also TVO and petrol engines.

Product Profile:

Massey Ferguson M1139, M1144, M1145
Ford M2C159B/C
New Holland NH 030 C and NH 024 C
John Deere J20C, J27
ZF TE ML 06 A,B & C, 07B
Allison C4
API GL-4 CG-4
Mercedes Benz 228.1
ACEA E3
MAN 271

Typical Test Data:

SAE Viscosity Grade	-	10w/30
Specific Gravity @ 16 °C	-	0.887
Kinematic Viscosity mm ² /S		
@40 °C	-	70.0
@100 °C	-	10.8
Viscosity Index (VI)	-	142
Pour Point °C	-	-38

V2 1115

Contact for more information.

Unit 10, Greenhills Business Centre, Greenhills Road, Tallaght, Dublin 24
Office contact
Email: info@bardahl.ie
Tel: 01 - 404 9490



A product of Bardahl Distributors.