



A product of **Bardahl** Distributors

40 Hibernian Industrial Estate, Greenhills Road,
Tallaght, Dublin. D24 DK07
Email: info@bardahl.ie
Tel: 01 - 404 9490

FORTECH 10W-40 (78005E)

Universal synthetic Motor oil

DESCRIPTION

FORTECH 10W-40 is a semi-synthetic engine oil recommended for petrol and diesel engines. Because of the high viscosity index, the oil assures an excellent coldstart as well as an excellent lubricating film with high temperatures.

FORTECH 10W-40 takes care of trouble free functioning of the engine, because of the chosen additive package. The oil helps reducing the fuel consumption as well as reducing emission levels. Because of the unique formulation a low evaporation under severe operating conditions is guaranteed.

In addition, FORTECH 10W-40 gives optimum protection against wear and has strong anti-corrosion and anti-foam characteristics as well as a high resistance against oxidation. Together with the excellent detergent/dispersant properties, this oil ensures a clean and reliable engine.

SPECIFICATIONS

Performance level:

API SL/CF
ACEA A3/B3

Recommended for use:

MB 229.1
VW 501.01/VW 505.00

PHYSICAL PROPERTIES

Colour	Brown	
Density at 20°C	0.8614 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	100.8 cSt	ASTM D 445
Viscosity, kinematic at 100°C	15 cSt	ASTM D 445
Viscosity Index	156	ASTM D 2270
Viscosity, dynamic (CCS)	5540 cP	ASTM D 2602
Base number	8.0 mg KOH/g	ASTM D 2896
Sulphated ash	0.95 wt%	ASTM D 874
Flash point	207 °C	ASTM D 93
Pour point	-39 °C	ASTM D 97

Version 2.2, 08-12-2017

This sheet contains recommendations or suggestions on properties and possible applications of Fortech products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.